

## Cleaning - Protecting - Maintaining

### Porcelain Tiles -indoors-

Instructions for matte, glazed and structured finishes

Porcelain tiles are made of very fine ceramic materials that are fired at high temperatures. This process leads to very dense, very robust tiles. The right treatment will bring the tiles to their full potential and ensures the ideal properties for many years.

#### Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1

#### Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin KF Cement Residue Remover leaves a clean and clear surface.



Coverage:  
1 Ltr./50m<sup>2</sup>



Dilute product 1:4  
with water.



Wipe surface with  
solution.



Rinse well with plenty  
of clear water and  
towel dry.

**Necessary equipment:** bucket, mop and scrubber, squeegee or wet-and-dry vacuum

2


#### Protecting against stains

A protective treatment is not required on matte, glazed and structured porcelain tiles.

3

#### Regular maintenance


Lithofin KF Conditioning Cleaner maintains porcelain tile surfaces.



Add one squirt (20ml)  
to one bucket of wa-  
ter.



Wipe surface with so-  
lution. Remove mois-  
ture with a well  
wrung-out mop.



Allow to dry. Do not  
walk on surface dur-  
ing drying time.

**Erforderliche Geräte:** Eimer, Wischmopp o.ä.

Please follow the detailed instructions on the product labels.

Ref. 22001 12.20gps

**1 Cleaning and refurbishing used or extremely dirty surfaces**

Before treating used surfaces, the stone must be thoroughly cleaned. All deposits and care product residues must be removed from the surface and from the pores.

- Dilute Lithofin KF Intensive Cleaner up to 1:10, apply using a scrubbing brush or a white pad and allow to work for 5 to 10 minutes.
  - Scrub well with a scrubbing brush or machine and wait 5 more min.  
 Add water and remove the solution with a mop or a wet-and-dry vacuum.
  - Rinse twice with plenty of clear water until all product residues are removed.
- Allow the surface to dry for 24 to 48 hours before applying a protective treatment.



**Other, stubborn types of dirt**

grease, oil, wax, varnish, paint, ink, rubber streaks, polymer layers, etc.	Lithofin WAX-OFF
calcium deposits, rust discolouration	Lithofin KF Ceramic-Clean
Coffee, tea, red wine, fruit juice	Lithofin KF Mildew-Away

**2 Additional maintenance in bathrooms**

Lithofin KF Ceramic-Clean dissolves surface deposits like calcium and dirt, water stains, greasy residues and rust. These substances can then be simply rinsed off with water. The pleasant odour supports hygienic cleanliness.

Please Note: to protect cement based grout lines, always pre-wet them with water and use Lithofin KF Ceramic-Clean only in diluted form.



**Advice:**

Black mould stains and mildew in cement or silicone joints can be removed with Lithofin KF Mildew-Away. Simply spray the surface and after approx. 30 minutes, rinse with water.



**Please Note:**

- △ Please follow the detailed instructions on the label.
- △ Greasy or waxy maintenance products may bind dirt and will affect the slip resistance properties of the surface.

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Instructions must be read carefully and followed closely. Always test the products in an inconspicuous area. (GB12.20gps)

If you require advice or are in any way unsure about these instructions, please call our **Technical Support Line at (01962) 732126.**

Your LITHOFIN-Dealer:

**The Professional Solution**

**Distribution in UK and Ireland:**

CASDRON Enterprises Ltd. · Alesford, Hampshire SO24 9QF · Phone: +44 (0)1962 732 126 · Fax +44 (0)1962 735 373  
 Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-mail: info@lithofin.de [www.lithofin.com](http://www.lithofin.com)