

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lithofin MN Colour Intensifier

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses

Mixture Impregnation, Contains: organic solvents

1.3 Details of the supplier of the safety data sheet

Distributor : Casdron Enterprises Ltd.
Street : Wood End, Prospect Road
Postal code/City : New Alresford, Hants SO 24 9QF
Land : GREAT BRITAIN
Telephone : +44 1962 732126
Telefax : +44 1962 735373
Contact : Technical Department
E-mail : sales@lithofin.co.uk

Emergency telephone number : **+44 1962 732126**
(Only available during office hours)

Supplier : Lithofin AG
Street : Heinrich-Otto-Str. 36
Postal code/City : 73240 Wendlingen
Country : GERMANY
Telephone : +49 7024 9403 0
Telefax : +49 7024 9403 40
Contact : Technical Department
E-mail : info@lithofin.de

Emergency telephone number : **+49 7024 9403 0**
(Only available during office hours)

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.
Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.
STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.
STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.
Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.
Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Remark

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

ETHYLBENZENE ; CAS No. : 100-41-4

Hazard statements

- | | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |

Precautionary statements

- | | |
|-----------|--|
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor/.... |
| P331 | Do NOT induce vomiting. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local and national regulations. |

Other labelling

2.3 Other hazards

Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

2.4 Additional information

see section 12.5

SECTION 3: Composition/information on ingredients

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

3.2 Mixtures

Hazardous ingredients

XYLENE ; REACH No. : 01-2119488216-32-xxxx ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction : $\geq 30 - < 35 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; REACH No. : 01-2119463258-33-xxxx ; EC No. : 919-857-5; CAS No. : (64742-48-9)

Weight fraction : $\geq 25 - < 30 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 EUH066

Hydrocarbons, C9, aromatics ; REACH No. : 01-2119455851-35-xxxx ; EC No. : 918-668-5; CAS No. : (64742-95-6)

Weight fraction : $\geq 15 - < 20 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 EUH066

ETHYLBENZENE ; REACH No. : 01-2119489370-35 ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 (auditory organs) Acute Tox. 4 ; H332 Aquatic Chronic 3 ; H412

ETHYL ACETATE ; REACH No. : 01-2119475103-46-xxxx ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066

TETRAETHYL SILICATE ; REACH No. : 01-2119496195-28-xxxx ; EC No. : 201-083-8; CAS No. : 78-10-4

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

None (below the concentration limit)

Contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH

None (below the concentration limit)

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

< 0,1% Benzene, Regulation (EC) No. 1272/2008, Annex VI; J, P

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice. Observe risk of aspiration if vomiting occurs.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

plenty of water (only if the person is conscious) and obtain immediate medical attention.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

Special treatment

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO₂) BC-powder ABC-powder Water spray jet

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

When using do not eat, drink, smoke, sniff.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists
Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition - No smoking. The product is: Combustible

Fire class : B

Shake well before use nein

Advices on general occupational hygiene

P362+P364 - Take off contaminated clothing and wash it before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Hints on joint storage

Storage class (TRGS 510) : 3

Protect from frost nein

Recommended storage temperature 5 - 25 °C

Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

7.3 Specific end use(s)

Recommendation

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : KZW (A)

Limit value : 100 ppm / 442 mg/m³

Peak limitation : 15Miw, 4x

Version :

Limit value type (country of origin) : TMW / TWA (A)

Limit value : 50 ppm / 221 mg/m³

Version :

Limit value type (country of origin) : STEL (AUS)

Limit value : 150 ppm / 655 mg/m³

Remark : OTO

Version :

Limit value type (country of origin) : TWA (AUS)

Limit value : 80 ppm / 350 mg/m³

Remark : OTO

Version :

Limit value type (country of origin) : STEL (B)

Limit value : 100 ppm / 442 mg/m³

Remark : D

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Version :

Limit value type (country of origin) : TWA (B)
Limit value : 50 ppm / 221 mg/m³
Remark : D
Version :

Limit value type (country of origin) : BAT (CH)
Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift
Limit value : 2 g/l
Version :

Limit value type (country of origin) : KZG / STEL (CH)
Limit value : 200 ppm / 870 mg/m³
Remark : H, B
Version :

Limit value type (country of origin) : MAK (CH)
Limit value : 100 ppm / 435 mg/m³
Remark : H, B
Version :

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 220 mg/m³
Peak limitation : 2(II)
Remark : H
Version : 04.11.2017

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift
Limit value : 1,5 mg/l
Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift
Limit value : 2 g/l
Version : 31.03.2004

Limit value type (country of origin) : TWA (DK)
Limit value : 25 ppm / 109 mg/m³
Remark : EH
Version :

Limit value type (country of origin) : VLA-EC / STEL (E)
Limit value : 100 ppm / 442 mg/m³
Remark : vía dérmica, VLB, VLI
Version :

Limit value type (country of origin) : VLA-ED / TWA (E)
Limit value : 50 ppm / 221 mg/m³
Remark : vía dérmica, VLB, VLI
Version :

Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 442 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 221 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : VLEP 8h / TWA (F)
Limit value : 50 ppm / 221 mg/m³
Version :

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Limit value type (country of origin) : VLEP CT / STEL (F)
Limit value : 100 ppm / 442 mg/m³
Version :

Limit value type (country of origin) : STEL (GB)
Limit value : 100 ppm / 441 mg/m³
Remark : Sk, BMGV
Version :

Limit value type (country of origin) : TWA (GB)
Limit value : 50 ppm / 220 mg/m³
Remark : Sk, BMGV
Version :

Limit value type (country of origin) : ÁK (H)
Limit value : 50 ppm / 221 mg/m³
Remark : b, BEM
Version :

Limit value type (country of origin) : CK-érték / STEL (H)
Limit value : 100 ppm / 442 mg/m³
Remark : b, BEM
Version :

Limit value type (country of origin) : STEL (I)
Limit value : 100 ppm / 442 mg/m³
Remark : Cute
Version :

Limit value type (country of origin) : TWA (I)
Limit value : 50 ppm / 221 mg/m³
Remark : Cute
Version :

Limit value type (country of origin) : OELV 15 min / STEL (IRL)
Limit value : 100 ppm / 442 mg/m³
Remark : Sk, IOELV
Version :

Limit value type (country of origin) : OELV 8h / TWA (IRL)
Limit value : 50 ppm / 221 mg/m³
Remark : Sk, IOELV
Version :

Limit value type (country of origin) : TWA (N)
Limit value : 25 ppm / 108 mg/m³
Remark : HE
Version :

Limit value type (country of origin) : TGG 15 min / STEL (NL)
Limit value : 100 ppm / 442 mg/m³
Remark : H
Version :

Limit value type (country of origin) : TGG 8 uur / TWA (NL)
Limit value : 47,5 ppm / 210 mg/m³
Remark : H
Version :

Limit value type (country of origin) : TWA (NZ)
Limit value : 50 ppm / 217 mg/m³
Remark : oto; bio
Version :

Limit value type (country of origin) : NDSCH (PL)
Limit value : 200 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Remark : skóra
Version :

Limit value type (country of origin) : NDS (PL)
Limit value : 100 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : STEL (ROK)
Limit value : 150 ppm
Version :

Limit value type (country of origin) : TWA (ROK)
Limit value : 100 ppm
Version :

Limit value type (country of origin) : ACGIH TLV (USA)
Limit value : 20 ppm
Remark : A4, OTO
Version :

Limit value type (country of origin) : OSHA PEL TWA (USA)
Limit value : 100 ppm / 435 mg/m³
Remark : Appendix G (STEL 150 ppm, 655 mg/m³)
Version :

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)
Limit value type (country of origin) : KZW (A)
Limit value : 400 ppm
Peak limitation : 30 Min, 4x
Version :

Limit value type (country of origin) : TMW / TWA (A)
Limit value : 200 ppm
Version :

Limit value type (country of origin) : KZG / STEL (CH)
Limit value : 100 ppm / 600 mg/m³
Version :

Limit value type (country of origin) : MAK (CH)
Limit value : 50 ppm / 300 mg/m³
Version :

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 300 mg/m³
Peak limitation : 2(II)
Version :

Limit value type (country of origin) : TWA (N)
Limit value : 50 ppm / 275 mg/m³
Remark : (White Spirit, < 22% aromatic compounds)
Version :

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)
Limit value type (country of origin) : KZW (A)
Limit value : 40 ppm
Peak limitation : 30 Min, 4x
Version :

Limit value type (country of origin) : TMW / TWA (A)
Limit value : 20 ppm
Version :

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 mg/m³
Peak limitation : 2(II)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Version :

Limit value type (country of origin) : TWA (GB)

Limit value : 500 mg/m³

Version :

Limit value type (country of origin) : TWA (N)

Limit value : 25 ppm / 120 mg/m³

Remark : (White Spirit, > 22% aromatic compounds)

Version :

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : KZW (A)

Limit value : 200 ppm / 880 mg/m³

Peak limitation : 5Mow, 8x

Remark : H

Version :

Limit value type (country of origin) : TMW / TWA (A)

Limit value : 100 ppm / 440 mg/m³

Remark : H

Version :

Limit value type (country of origin) : TWA (AUS)

Limit value : 20 ppm / 87 mg/m³

Remark : OTO

Version :

Limit value type (country of origin) : STEL (B)

Limit value : 125 ppm / 551 mg/m³

Remark : D

Version :

Limit value type (country of origin) : TWA (B)

Limit value : 20 ppm / 87 mg/m³

Remark : D

Version :

Limit value type (country of origin) : BAT (CH)

Parameter : Urine (U) / End of exposure or end of shift

Limit value : 600 mg/g Creatinine

Version :

Limit value type (country of origin) : KZG / STEL (CH)

Limit value : 50 ppm / 220 mg/m³

Remark : H, OL, B

Version :

Limit value type (country of origin) : MAK (CH)

Limit value : 50 ppm / 220 mg/m³

Remark : H, OL, B

Version :

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 20 ppm / 88 mg/m³

Peak limitation : 2(II)

Remark : H, Y

Version : 17.06.2024

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift

Limit value : 250 mg/g Creatinine

Version : 10.10.2024

Limit value type (country of origin) : TWA (DK)

Limit value : 50 ppm / 217 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Remark : EHK
Version :

Limit value type (country of origin) : VLA-EC / STEL (E)
Limit value : 200 ppm / 884 mg/m³
Remark : via dérmica, VLB, VLI
Version :

Limit value type (country of origin) : VLA-ED / TWA (E)
Limit value : 100 ppm / 441 mg/m³
Remark : via dérmica, VLB, VLI
Version :

Limit value type (country of origin) : STEL (EC)
Limit value : 200 ppm / 884 mg/m³
Remark : Skin
Version : 09.03.2022

Limit value type (country of origin) : TWA (EC)
Limit value : 100 ppm / 442 mg/m³
Remark : Skin
Version : 09.03.2022

Limit value type (country of origin) : VLEP 8h / TWA (F)
Limit value : 20 ppm / 88,4 mg/m³
Version :

Limit value type (country of origin) : VLEP CT / STEL (F)
Limit value : 100 ppm / 442 mg/m³
Version :

Limit value type (country of origin) : STEL (GB)
Limit value : 125 ppm / 552 mg/m³
Remark : Sk
Version :

Limit value type (country of origin) : TWA (GB)
Limit value : 100 ppm / 441 mg/m³
Remark : Sk
Version :

Limit value type (country of origin) : ÁK (H)
Limit value : 100 ppm / 442 mg/m³
Remark : b, i, BEM
Version :

Limit value type (country of origin) : CK-érték / STEL (H)
Limit value : 200 ppm / 884 mg/m³
Remark : b, i, BEM
Version :

Limit value type (country of origin) : STEL (I)
Limit value : 200 ppm / 884 mg/m³
Remark : Cute
Version :

Limit value type (country of origin) : TWA (I)
Limit value : 100 ppm / 442 mg/m³
Remark : Cute
Version :

Limit value type (country of origin) : OELV 15 min / STEL (IRL)
Limit value : 200 ppm / 884 mg/m³
Remark : Sk, IOELV
Version :

Limit value type (country of origin) : OELV 8h / TWA (IRL)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Limit value : 100 ppm / 442 mg/m³
Remark : Sk IOELV
Version :

Limit value type (country of origin) : TWA (N)
Limit value : 5 ppm / 20 mg/m³
Remark : HKE
Version :

Limit value type (country of origin) : TGG 15 min / STEL (NL)
Limit value : 97,3 ppm / 430 mg/m³
Remark : H
Version :

Limit value type (country of origin) : TGG 8 uur / TWA (NL)
Limit value : 48,6 ppm / 215 mg/m³
Remark : H
Version :

Limit value type (country of origin) : STEL (NZ)
Limit value : 40 ppm / 176 mg/m³
Remark : skin; oto
Version :

Limit value type (country of origin) : TWA (NZ)
Limit value : 20 ppm / 88 mg/m³
Remark : skin; oto
Version :

Limit value type (country of origin) : NDSCH (PL)
Limit value : 400 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : NDS (PL)
Limit value : 200 mg/m³
Remark : skóra
Version :

Limit value type (country of origin) : STEL (ROK)
Limit value : 125 ppm
Remark : 발암성 2
Version :

Limit value type (country of origin) : TWA (ROK)
Limit value : 100 ppm
Remark : 발암성 2
Version :

Limit value type (country of origin) : ACGIH TLV (USA)
Limit value : 20 ppm
Remark : A3, OTO
Version :

Limit value type (country of origin) : NIOSH REL STEL (USA)
Limit value : 125 ppm / 545 mg/m³
Version :

Limit value type (country of origin) : NIOSH REL TWA (USA)
Limit value : 100 ppm / 435 mg/m³
Version :

Limit value type (country of origin) : OSHA PEL TWA (USA)
Limit value : 100 ppm / 435 mg/m³
Remark : see Appendix G (STEL 125 ppm)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Version :

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type (country of origin) : KZW (A)

Limit value : 400 ppm / 1468 mg/m³

Peak limitation : 15Miw, 4x

Version :

Limit value type (country of origin) : TMW / TWA (A)

Limit value : 200 ppm / 734 mg/m³

Version :

Limit value type (country of origin) : STEL (AUS)

Limit value : 800 ppm / 1500 mg/m³

Version :

Limit value type (country of origin) : TWA (AUS)

Limit value : 200 ppm / 720 mg/m³

Version :

Limit value type (country of origin) : STEL (B)

Limit value : 400 ppm / 1468 mg/m³

Version :

Limit value type (country of origin) : TWA (B)

Limit value : 200 ppm / 734 mg/m³

Version :

Limit value type (country of origin) : KZG / STEL (CH)

Limit value : 400 ppm / 1460 mg/m³

Remark : SSc

Version :

Limit value type (country of origin) : MAK (CH)

Limit value : 200 ppm / 730 mg/m³

Remark : SSc

Version :

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 200 ppm / 730 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 17.06.2024

Limit value type (country of origin) : TWA (DK)

Limit value : 150 ppm / 540 mg/m³

Remark : E

Version :

Limit value type (country of origin) : VLA-EC / STEL (E)

Limit value : 400 ppm / 1468 mg/m³

Remark : VLI

Version :

Limit value type (country of origin) : VLA-ED / TWA (E)

Limit value : 200 ppm / 734 mg/m³

Remark : VLI

Version :

Limit value type (country of origin) : VLEP 8h / TWA (F)

Limit value : 200 ppm / 734 mg/m³

Version :

Limit value type (country of origin) : VLEP CT / STEL (F)

Limit value : 400 ppm / 1468 mg/m³

Version :

Limit value type (country of origin) : STEL (GB)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Limit value : 400 ppm / 1468 mg/m³
Version :

Limit value type (country of origin) : TWA (GB)
Limit value : 200 ppm / 734 mg/m³
Version :

Limit value type (country of origin) : ÁK (H)
Limit value : 200 ppm / 734 mg/m³
Remark : i, sz
Version :

Limit value type (country of origin) : CK-érték / STEL (H)
Limit value : 400 ppm / 1468 mg/m³
Remark : i, sz
Version :

Limit value type (country of origin) : STEL (I)
Limit value : 400 ppm / 1468 mg/m³
Version :

Limit value type (country of origin) : TWA (I)
Limit value : 200 ppm / 734 mg/m³
Version :

Limit value type (country of origin) : OELV 15 min / STEL (IRL)
Limit value : 400 ppm / 1468 mg/m³
Remark : IOELV
Version :

Limit value type (country of origin) : OELV 8h / TWA (IRL)
Limit value : 200 ppm / 734 mg/m³
Remark : IOELV
Version :

Limit value type (country of origin) : STEL (N)
Limit value : 400 ppm / 1468 mg/m³
Remark : S
Version :

Limit value type (country of origin) : TWA (N)
Limit value : 200 ppm / 734 mg/m³
Remark : E
Version :

Limit value type (country of origin) : TGG 15 min / STEL (NL)
Limit value : 400 ppm / 1468 mg/m³
Version :

Limit value type (country of origin) : TGG 8 uur / TWA (NL)
Limit value : 200 ppm / 734 mg/m³
Version :

Limit value type (country of origin) : TWA (NZ)
Limit value : 200 ppm / 720 mg/m³
Version :

Limit value type (country of origin) : NDSCH (PL)
Limit value : 1468 mg/m³
Version :

Limit value type (country of origin) : NDS (PL)
Limit value : 734 mg/m³
Version :

Limit value type (country of origin) : TWA (ROK)
Limit value : 400 ppm
Version :

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Limit value type (country of origin) : ACGIH TLV (USA)
Limit value : 400 ppm / 1440 mg/m³
Version :

Limit value type (country of origin) : NIOSH REL TWA (USA)
Limit value : 400 ppm / 1400 mg/m³
Version :

Limit value type (country of origin) : OSHA PEL TWA (USA)
Limit value : 400 ppm / 1400 mg/m³
Version :

TETRAETHYL SILICATE ; CAS No. : 78-10-4

Limit value type (country of origin) : KZW (A)
Limit value : 10 ppm / 88 mg/m³
Peak limitation : 5Mow, 8x
Version :

Limit value type (country of origin) : TMW / TWA (A)
Limit value : 5 ppm / 44 mg/m³
Version :

Limit value type (country of origin) : TWA (AUS)
Limit value : 5 ppm / 44 mg/mg
Version :

Limit value type (country of origin) : TWA (B)
Limit value : 5 ppm / 44 mg/m³
Version :

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1,4 ppm / 12 mg/m³
Peak limitation : 1(I)
Version : 17.06.2024

Limit value type (country of origin) : TWA (DK)
Limit value : 5 ppm / 44 mg/m³
Remark : E
Version :

Limit value type (country of origin) : VLA-ED / TWA (E)
Limit value : 5 ppm / 44 mg/m³
Remark : VLI
Version :

Limit value type (country of origin) : TWA (EC)
Limit value : 44 mg/m³ / 5 ppm
Version : 09.03.2022

Limit value type (country of origin) : VLEP 8h / TWA (F)
Limit value : 5 ppm / 44 mg/m³
Version :

Limit value type (country of origin) : TWA (GB)
Limit value : 5 ppm / 44 mg/m³
Version :

Limit value type (country of origin) : ÁK (H)
Limit value : 5 ppm / 44 mg/m³
Remark : i
Version :

Limit value type (country of origin) : TWA (I)
Limit value : 5 ppm / 44 mg/m³
Version :

Limit value type (country of origin) : OELV 8h / TWA (IRL)
Limit value : 5 ppm / 44 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Remark : IOELV
Version :
Limit value type (country of origin) : TWA (N)
Limit value : 5 ppm / 44 mg/m³
Remark : E
Version :
Limit value type (country of origin) : TGG 8 uur / TWA (NL)
Limit value : 5 ppm / 44 mg/m³
Version :
Limit value type (country of origin) : TWA (NZ)
Limit value : 10 ppm / 85 mg/m³
Version :
Limit value type (country of origin) : NDS (PL)
Limit value : 44 mg/m³
Version :
Limit value type (country of origin) : TWA (ROK)
Limit value : 10 ppm
Version :
Limit value type (country of origin) : ACGIH TLV (USA)
Limit value : 10 ppm / 85 mg/m³
Version :
Limit value type (country of origin) : NIOSH REL TWA (USA)
Limit value : 10 ppm / 85 mg/m³
Version :
Limit value type (country of origin) : OSHA PEL TWA (USA)
Limit value : 100 ppm / 850 mg/m³
Remark : see Appendix G (TWA 10 ppm)
Version :

DNEL-/PNEC-values

DNEL/DMEL

XYLENE ; CAS No. : 1330-20-7

Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 260 mg/m³
Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 65,3 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 5 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 125 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 260 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Exposure frequency :	Long-term
Limit value :	65,3 mg/m ³
Limit value type :	DNEL worker (local)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	442 mg/m ³
Limit value type :	DNEL worker (local)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	221 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	212 mg/kg bw/day
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	442 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	221 mg/m ³

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9)

Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	125 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	125 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	185 mg/m ³
Limit value type :	DNEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	208 mg/kg bw/day
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	871 mg/m ³

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

Limit value type :	DNEL Consumer (systemic)
Exposure route :	Oral
Exposure frequency :	Long-term
Limit value :	11 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	11 mg/kg bw/day
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Limit value : 32 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 25 mg/kg
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 150 mg/m³

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 1,6 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 15 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 293 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 180 mg/kg bw/day
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 77 mg/m³

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 734 mg/m³
Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 367 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 4,5 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 37 mg/kg bw/day
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 734 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 367 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 1468 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 734 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 63 mg/kg bw/day
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 1468 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 734 mg/m³

PNEC

XYLENE ; CAS No. : 1330-20-7

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,044 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 0,01 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,004 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 2,52 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 2,52 mg/kg dw
Limit value type : PNEC (Soil)
Limit value : 0,852 mg/kg dw
Limit value type : PNEC (Sewage treatment plant)
Limit value : 1,6 mg/l

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,1 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,01 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 13,7 mg/kg dw
Limit value type : PNEC (Sediment, marine water)
Limit value : 1,37 mg/kg dw
Limit value type : PNEC (Soil)
Limit value : 2,68 mg/kg dw
Limit value type : PNEC (Sewage treatment plant)
Limit value : 9,6 mg/l

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,24 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Limit value : 1,65 mg/l
Limit value type : PNEC (Aquatic, marine water)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Limit value :	0,024 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Limit value :	1,15 mg/kg dw
Limit value type :	PNEC (Sediment, marine water)
Limit value :	0,115 mg/kg dw
Limit value type :	PNEC (Soil)
Limit value :	0,148 mg/kg dw
Limit value type :	PNEC (Sewage treatment plant)
Limit value :	650 mg/l

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection goggles

Required properties

EN 166

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : Data apply to the main component. FKM (fluoro rubber), 0,7mm, >8h;

Required properties : EN ISO 374

Recommended glove articles : Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures : Check leak tightness/impermeability prior to use.

Remark : Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

Body protection

Protective clothing.

Suitable protective clothing : Chemical protection clothing Chemical resistant safety shoes

Required properties : antistatic.

Protective clothing. : EN 13034 EN 14605

Chemical resistant safety shoes : EN ISO 20345

Remark : Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (EN 136/140) Combination filtering device ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General information

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid

Colour : colourless

Odour : solvent

Safety characteristics

Melting point/freezing point : (1013 hPa) < -18 °C

Initial boiling point and boiling range : (1013 hPa) approx. 143 °C

Decomposition temperature : (1013 hPa) not determined

Flash point : approx. 26,5 °C closed cup (EN ISO 3679)

Auto-ignition temperature : not determined

Sustaining combustion Yes UN Test L2:Sustained combustibility test

Lower explosion limit : not determined

Upper explosion limit : not determined

Vapour pressure : (50 °C) < 3000 hPa

Density : (20 °C) 0,86 g/cm³ Pyknometer (DIN EN ISO 2811-1)

Relative density : (20 °C) not determined

Solvent separation test : (20 °C) < 3 % Test L1: Solvent separation test (UN)

Water solubility (20 °C) hydrolysed

Fat solubility : (20 °C) Not determined.

pH : not applicable DIN 19268

log P O/W : not determined (Mixture) ISO cup 4 mm (DIN EN ISO 2431)

Flow time : (23 °C) approx. 14 s

Odour threshold : not determined

Vapourisation rate : not determined

VOC content-EC 87,4 Weight-% *

VOC content-EC 747 g/l *

VOC-France A+ Décret no 2011-321 du 23 mars 2011

Flammable solids : Not determined.

(* VOC-EC = „Volatile organic compound (VOC)“ means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

9.2 Other information

Data apply to the main component:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS: 64742-48-9)

Lower explosion limit (Vol-%): 0,6

Upper explosion limit (Vol-%): 6,0

log P O/W: 5,0 - 6,7

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

Parameter :	LD50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	3523 mg/kg
Parameter :	LD50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 - 5000 mg/kg
Parameter :	LD50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	3500 mg/kg
Parameter :	LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route :	Oral
Species :	Rat
Effective dose :	5620 mg/kg
Parameter :	LD50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Method :	OECD 423

Acute dermal toxicity

Parameter :	LD50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	12126 mg/kg
Parameter :	LD50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Exposure route :	Dermal

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Species : Rabbit
Effective dose : > 2000 mg/kg
Method : OECD 402
Parameter : LD50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Exposure route : Dermal
Species : Rabbit
Effective dose : 15400 mg/kg
Parameter : LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 20000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (XYLENE ; CAS No. : 1330-20-7)
Exposure route : Inhalation
Species : Rat
Effective dose : 27124 mg/m³
Exposure time : 4 h
Parameter : LC50 (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Exposure route : Inhalation
Species : Rat
Effective dose : > 2 - 10 mg/l
Exposure time : 4 h
Method : OECD 403
Parameter : LC50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Exposure route : Inhalation
Species : Rat
Effective dose : 17629 mg/m³
Exposure time : 4 h
Parameter : LC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Species : Rat
Effective dose : > 22,5 mg/l
Exposure time : 6 h
Parameter : LC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Exposure route : Inhalation
Species : Rat
Effective dose : 10 mg/l
Exposure time : 4 h
Method : OECD 403

Specific effects (Longterm animal experiment)

There are no data available on the preparation/mixture itself.

Corrosion

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Repeated dose toxicity (subacute, subchronic, chronic)

There are no data available on the preparation/mixture itself.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Harmful to aquatic life with long lasting effects.

Acute (short-term) fish toxicity

Parameter : LC50 (XYLENE ; CAS No. : 1330-20-7)

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 2,6 mg/l

Exposure time : 96 hour(s)

Parameter : LC50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : > 1000 mg/l

Exposure time : 96 hour(s)

Method : OECD 203

Parameter : LC50 (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 9,2 mg/l

Exposure time : 96 hour(s)

Method : OECD 203

Parameter : LC50 (ETHYLBENZENE ; CAS No. : 100-41-4)

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 4,2 mg/l

Exposure time : 96 hour(s)

Parameter : LC50 (ETHYL ACETATE ; CAS No. : 141-78-6)

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 230 mg/l

Exposure time : 96 hour(s)

Parameter : LC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : > 245 mg/l

Exposure time : 96 hour(s)

Method : OECD 203

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Chronic (long-term) fish toxicity

Parameter : NOEC (XYLENE ; CAS No. : 1330-20-7)
Species : Fish
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : 0,714 mg/l
Parameter : NOEC (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Fish
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : 0,131 mg/l
Exposure time : 28 day(s)
Parameter : NOEC (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Species : Fish
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : 1,23 mg/l
Exposure time : 28 day(s)
Parameter : NOEC (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Fish
Evaluation parameter : Chronic (long-term) fish toxicity
Effective dose : > 2,4 mg/l
Exposure time : 21 day(s)

Acute (short-term) toxicity to aquatic invertebrates

Parameter : EC50 (XYLENE ; CAS No. : 1330-20-7)
Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates
Effective dose : 1 mg/l
Exposure time : 48 hour(s)
Parameter : EC50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates
Effective dose : > 1000 mg/l
Exposure time : 48 hour(s)
Method : OECD 202
Parameter : EC50 (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates
Effective dose : 3,2 mg/l
Exposure time : 48 hour(s)
Method : OECD 202
Parameter : EC50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates
Effective dose : 1,8 mg/l
Exposure time : 48 hour(s)
Parameter : EC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates
Effective dose : 165 mg/l
Exposure time : 48 hour(s)
Parameter : EC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Species : Daphnia
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates
Effective dose : > 75 mg/l
Exposure time : 48 hour(s)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Method : OECD 202

Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC (XYLENE ; CAS No. : 1330-20-7)
Species : Daphnia
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 0,96 mg/l
Parameter : NOEC (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Daphnia
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 0,23 mg/l
Exposure time : 21 day(s)
Parameter : NOEC (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Species : Daphnia
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 2,14 mg/l
Exposure time : 21 day(s)
Parameter : NOEC (ETHYLBENZENE ; CAS No. : 100-41-4)
Species : Daphnia
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 1 mg/l
Parameter : NOEC (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Daphnia
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate
Effective dose : 2,4 mg/l
Exposure time : 21 day(s)

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (XYLENE ; CAS No. : 1330-20-7)
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 4,36 mg/l
Exposure time : 72 hour(s)
Parameter : EC50 (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; CAS No. : (64742-48-9))
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 1000 mg/l
Exposure time : 72 hour(s)
Method : OECD 201
Parameter : EC50 (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 3,8 mg/l
Exposure time : 72 hour(s)
Method : OECD 201
Parameter : EC50 (ETHYLBENZENE ; CAS No. : 100-41-4)
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 3,6 mg/l
Exposure time : 72 hour(s)
Parameter : EC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : 5600 mg/l
Exposure time : 48 hour(s)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

Parameter : EC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Species : Algae
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria
Effective dose : > 100 mg/l
Exposure time : 72 hour(s)

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC (XYLENE ; CAS No. : 1330-20-7)
Species : Algae
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria
Effective dose : 0,44 mg/l
Parameter : NOEC (Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6))
Species : Algae
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria
Effective dose : 0,07 mg/l
Exposure time : 72 hour(s)
Parameter : NOEC (ETHYLBENZENE ; CAS No. : 100-41-4)
Species : Algae
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria
Effective dose : 3,4 mg/l
Parameter : NOEC (ETHYL ACETATE ; CAS No. : 141-78-6)
Species : Algae
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria
Effective dose : > 1000 mg/l
Exposure time : 48 hour(s)
Method : OECD 201
Parameter : NOEC (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Species : Algae
Effective dose : >= 100 mg/l

Sewage treatment plant

Observe local regulations concerning effluent treatment.

12.2 Persistence and degradability

There are no data available on the preparation/mixture itself.

Biodegradation

There are no data available on the preparation/mixture itself.

12.3 Bioaccumulative potential

There are no data available on the preparation/mixture itself.

12.4 Mobility in soil

There are no data available on the preparation/mixture itself.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

There are no data available on the preparation/mixture itself.

12.8 Additional ecotoxicological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Dispose of waste according to applicable legislation.
Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Waste codes/waste designations according to EWC/AVV

Waste code (EWC/AVV) : 07 01 04* (other organic solvents, washing liquids and mother liquors)

After intended use

Do not allow to enter into surface water or drains. Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Delivery to an approved waste disposal company.

Disposal operations

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

Waste codes/waste designations according to EWC/AVV

Waste code packaging: 15 01 10*

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number or ID number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · XYLENE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · XYLENE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE · XYLENE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special Provisions : 640E · LQ 5 I · E 1
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special Provisions : LQ 5 I · E 1
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special Provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

Not required.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures (clp)

DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste (2000/532/EC)
EN 2:1992 (DIN EN 2:2005-01)

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 75

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Other regulations (EU)

Regulation (EC) No. 648/2004 [Detergents regulation]

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

Regulation (EU) 2024/590 on substances that deplete the ozone layer

Not listed/not relevant.

Contains the following substances that deplete the ozone layer: -

Regulation (EC) 2019/1021 [POP Regulation]

Not listed/not relevant.

Name of the persistent organic pollutant (POP): -

Regulation (EU) 2019/1148 (marketing and use of explosives precursors)

Not listed/not relevant.

Regulation (EU) 649/2012 (PIC)

Not listed/not relevant.

Chemicals qualifying for PIC notification: -

National regulations

Observe in addition any national regulations!

Germany:

TRGS 400 (Risk assessment for activities involving hazardous substances)

TRGS 500 (Protective measures)

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

Other regulations, restrictions and prohibition regulations

Switzerland

VOCV-Regulation

Maximum VOC content (Switzerland) : 87,4 Weight-% according to VOCV

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025

Version (Revision) :

7.0.0 (6.0.0)

Print date : 11.07.2025

15.2 Chemical Safety Assessment

For this substance/mixture a chemical safety assessment has not been carried out.

15.3 Additional information

SECTION 16: Other information

16.1 Indication of changes

02. Label elements · 03. Hazardous ingredients · 08. Occupational exposure limit values

16.2 Abbreviations and acronyms

ABC-Pulver	Extinguishing powder for fire class A, B and C
ABEK-P1	combination filter
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AVV	Abfallverzeichnis-Verordnung (Waste Regulation)
AWSV	Ordinance on facilities for the handling of substances hazardous to water
BGR	BG rules and regulations
ca.	circa
CAS	Chemical Abstracts Service
CLP	classification, labelling and packaging
CMR	Carcinogen, mutagen or toxic for reproduction
DIN	German Institute for Standardization
DNEL	Derived No-Effect Level
EAK/EWC/EAC/CWR/CER	European Waste Catalogue
EC50 / CE50	Effective Concentration 50%
EG / EC / CE	European Community
EN	European Standard
EUH	supplemental hazard statement of the european union
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)
GHS / SGH	Globally Harmonised System
H-Sätze	hazard statements
IATA-DGR	International Air Transport Association-Dangerous Goods Regulations
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization-Technical Instructions
IMDG-Code	International Maritime Dangerous Goods Code
ISO	International Organization for Standardization
LC50 / CL50	Lethal Concentration 50%
LD50 / DL50	Lethal Dose 50%
log P O/W	Partition coefficient n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (marine pollution)
NOAEL (DSET)	No observed adverse effect level
NOEC (CSEO)	No observed effect concentration
Nr.	Number
OECD	Organisation for Economic Co-operation and Development
PBT	persistent, bioaccumulative and toxic
pH	Potentia hydrogenii

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin MN Colour Intensifier

Revision date : 04.06.2025
Print date : 11.07.2025

Version (Revision) : 7.0.0 (6.0.0)

PIC	prior informed consent
PNEC	Predicted No-Effect Concentration
POP	Persistent organic pollutants
P-Sätze	precautionary statements
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	International Carriage of Dangerous Goods by Rail
STEL / LECT	short-term exposure limit
TRGS	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
TWA / MPT	time-weighted average
UN/ONU	United Nations
VOC/COV/VOS/LZO	Volatile Organic Compound
VOCV	Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)
vPvB	very persistent and very bioaccumulative
WGK	Wassergefährdungsklasse (Water hazard class)

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
ECHA: Registered substances (<https://echa.europa.eu/information-on-chemicals/registered-substances>)
REACH Article 59: Candidate List of substances of very high concern for Authorisation
(<https://echa.europa.eu/candidate-list-table>)

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data.
Hazard statements for health hazards : Calculation method.
Hazard statements for environmental hazards : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily

Safety Data Sheet

(EN / D)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : **Lithofin MN Colour Intensifier**

Revision date : 04.06.2025

Version (Revision) : 7.0.0 (6.0.0)

Print date : 11.07.2025

valid for the new made-up material.

(EN / D)