

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

Revision date : 04.06.2025

Version (Revision) : 6.0.0 (5.2.2)

Print date : 11.07.2025

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Lithofin MN Flagstone-Sealant

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Mixture Sealer, Contains: organic solvents

**1.3 Details of the supplier of the safety data sheet**

**Distributor :** Casdron Enterprises Ltd.  
**Street :** Wood End, Prospect Road  
**Postal code/City :** New Alresford, Hants SO 24 9QF  
**Land :** GREAT BRITAIN  
**Telephone :** +44 1962 732126  
**Telefax :** +44 1962 735373  
**Contact :** Technical Department  
**E-mail :** sales@lithofin.co.uk

**Emergency telephone number :** **+44 1962 732126**  
(Only available during office hours)

**Supplier :** Lithofin AG  
**Street :** Heinrich-Otto-Str. 36  
**Postal code/City :** 73240 Wendlingen  
**Country :** GERMANY  
**Telephone :** +49 7024 9403 0  
**Telefax :** +49 7024 9403 40  
**Contact :** Technical Department  
**E-mail :** info@lithofin.de

**Emergency telephone number :** **+49 7024 9403 0**  
(Only available during office hours)

**1.4 Emergency telephone number**

see section 1.3

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

**Additional information**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Flagstone-Sealant

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## Remark

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## 2.2 Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### Hazard pictograms



Flame (GHS02) · Environment (GHS09) · Exclamation mark (GHS07)

#### Signal word

Warning

#### Hazard components for labelling

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

#### Hazard statements

|      |                                                  |
|------|--------------------------------------------------|
| H226 | Flammable liquid and vapour.                     |
| H315 | Causes skin irritation.                          |
| H335 | May cause respiratory irritation.                |
| H336 | May cause drowsiness or dizziness.               |
| H411 | Toxic to aquatic life with long lasting effects. |

#### Precautionary statements

|           |                                                                                                |
|-----------|------------------------------------------------------------------------------------------------|
| P102      | Keep out of reach of children.                                                                 |
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P271      | Use only outdoors or in a well-ventilated area.                                                |
| P332+P313 | If skin irritation occurs: Get medical advice/attention.                                       |
| P405      | Store locked up.                                                                               |
| P501      | Dispose of contents/container in accordance with local and national regulations.               |

#### Special rules for supplemental label elements for certain mixtures

|        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUH208 | Contains Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL- HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXPHE- NYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPPLY(OXYETHYLENE).May produce an allergic reaction. |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Other labelling

## 2.3 Other hazards

### Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

### Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 2.4 Additional information

see section 12.5

**Trade name : Lithofin MN Flagstone-Sealant**

Revision date : 04.06.2025  
Print date : 11.07.2025

Version (Revision) : 6.0.0 (5.2.2)

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous ingredients**

Hydrocarbons, C9, aromatics ; REACH No. : 01-2119455851-35-xxxx ; EC No. : 918-668-5; CAS No. : (64742-95-6)

Weight fraction :  $\geq 60 - < 65 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 EUH066

XYLENE ; REACH No. : 01-2119488216-32-xxxx ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 15 - < 20 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

ETHYLBENZENE ; REACH No. : 01-2119489370-35 ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction :  $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 (auditory organs) Acute Tox. 4 ; H332 Aquatic Chronic 3 ; H412

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; REACH No. : 01-2119491304-40-xxxx ; EC No. : 915-687-0; CAS No. : 1065336-91-5

Weight fraction :  $\geq 0,25 - < 0,5 \%$

Classification 1272/2008 [CLP] : Repr. 2 ; H361d Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL- HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXYPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHE- NYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPLY(OXYETHYLENE) ; REACH No. : 01-0000015075-76-xxxx ; EC No. : 400-830-7

Weight fraction :  $\geq 0,1 - < 0,5 \%$

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

**Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH**

None (below the concentration limit)

**Contains the following substances of very high concern (SVHC) which are subject to authorisation according to Annex XIV of REACH**

None (below the concentration limit)

**Additional information**

All ingredients of this mixture are (pre)registered according to REACH regulation.

< 0,1% Benzene, Regulation (EC) No. 1272/2008, Annex VI; J, P

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious but breathing normally, place in recovery position and seek medical advice. Observe risk of aspiration if vomiting occurs.

**Following inhalation**

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

**In case of skin contact**

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

**After eye contact**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart

**Trade name : Lithofin MN Flagstone-Sealant**

Revision date : 04.06.2025

Version (Revision) : 6.0.0 (5.2.2)

Print date : 11.07.2025

and consult an ophthalmologist. Protect uninjured eye.

**Following ingestion**

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

No information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor**

Treat symptomatically.

**Special treatment**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Foam Carbon dioxide (CO2) BC-powder ABC-powder Water spray jet

**Unsuitable extinguishing media**

Full water jet Strong water jet

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

Carbon monoxide Carbon dioxide (CO2)

**5.3 Advice for firefighters**

Use suitable breathing apparatus.

**Special protective equipment for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**5.4 Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

**6.2 Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

**6.3 Methods and material for containment and cleaning up**

**For cleaning up**

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

**6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025  
**Print date :** 11.07.2025

**Version (Revision) :** 6.0.0 (5.2.2)

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

When using do not eat, drink, smoke, sniff.

**Protective measures**

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Wear personal protection equipment (refer to section 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

**Measures to prevent fire**

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition - No smoking. The product is: Combustible

**Fire class :** B

**Shake well before use** nein

**Advices on general occupational hygiene**

P362+P364 - Take off contaminated clothing and wash it before reuse.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep/Store only in original container. The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

**Hints on joint storage**

**Storage class (TRGS 510) :** 3

**Protect from frost** nein

**Recommended storage temperature** 5 - 25 °C

**Further information on storage conditions**

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

**7.3 Specific end use(s)**

**Recommendation**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

Limit value type (country of origin) : KZW ( A )

Limit value : 40 ppm

Peak limitation : 30 Min, 4x

Version :

Limit value type (country of origin) : TMW / TWA ( A )

Limit value : 20 ppm

Version :

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 mg/m<sup>3</sup>

Peak limitation : 2(II)

Version :

Limit value type (country of origin) : TWA ( GB )

Limit value : 500 mg/m<sup>3</sup>

Version :

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

Limit value type (country of origin) : TWA ( N )

Limit value : 25 ppm / 120 mg/m<sup>3</sup>

Remark : (White Spirit, > 22% aromatic compounds)

Version :

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : KZW ( A )

Limit value : 100 ppm / 442 mg/m<sup>3</sup>

Peak limitation : 15Miw, 4x

Version :

Limit value type (country of origin) : TMW / TWA ( A )

Limit value : 50 ppm / 221 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : STEL ( AUS )

Limit value : 150 ppm / 655 mg/m<sup>3</sup>

Remark : OTO

Version :

Limit value type (country of origin) : TWA ( AUS )

Limit value : 80 ppm / 350 mg/m<sup>3</sup>

Remark : OTO

Version :

Limit value type (country of origin) : STEL ( B )

Limit value : 100 ppm / 442 mg/m<sup>3</sup>

Remark : D

Version :

Limit value type (country of origin) : TWA ( B )

Limit value : 50 ppm / 221 mg/m<sup>3</sup>

Remark : D

Version :

Limit value type (country of origin) : BAT ( CH )

Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift

Limit value : 2 g/l

Version :

Limit value type (country of origin) : KZG / STEL ( CH )

Limit value : 200 ppm / 870 mg/m<sup>3</sup>

Remark : H, B

Version :

Limit value type (country of origin) : MAK ( CH )

Limit value : 100 ppm / 435 mg/m<sup>3</sup>

Remark : H, B

Version :

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 ppm / 220 mg/m<sup>3</sup>

Peak limitation : 2(II)

Remark : H

Version : 04.11.2017

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Xylene / Whole blood (B) / End of exposure or end of shift

Limit value : 1,5 mg/l

Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 ( D )

Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift

Limit value : 2 g/l

Version : 31.03.2004

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

---

Limit value type (country of origin) : TWA ( DK )  
Limit value : 25 ppm / 109 mg/m<sup>3</sup>  
Remark : EH  
Version :

Limit value type (country of origin) : VLA-EC / STEL ( E )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : via dérmica, VLB, VLI  
Version :

Limit value type (country of origin) : VLA-ED / TWA ( E )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : via dérmica, VLB, VLI  
Version :

Limit value type (country of origin) : STEL ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

Limit value type (country of origin) : VLEP 8h / TWA ( F )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Version :

Limit value type (country of origin) : VLEP CT / STEL ( F )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Version :

Limit value type (country of origin) : STEL ( GB )  
Limit value : 100 ppm / 441 mg/m<sup>3</sup>  
Remark : Sk, BMGV  
Version :

Limit value type (country of origin) : TWA ( GB )  
Limit value : 50 ppm / 220 mg/m<sup>3</sup>  
Remark : Sk, BMGV  
Version :

Limit value type (country of origin) : ÁK ( H )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : b, BEM  
Version :

Limit value type (country of origin) : CK-érték / STEL ( H )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : b, BEM  
Version :

Limit value type (country of origin) : STEL ( I )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Cute  
Version :

Limit value type (country of origin) : TWA ( I )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : Cute  
Version :

Limit value type (country of origin) : OELV 15 min / STEL ( IRL )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Sk, IOELV

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

Version :

Limit value type (country of origin) : OELV 8h / TWA ( IRL )

Limit value : 50 ppm / 221 mg/m<sup>3</sup>

Remark : Sk, IOELV

Version :

Limit value type (country of origin) : TWA ( N )

Limit value : 25 ppm / 108 mg/m<sup>3</sup>

Remark : HE

Version :

Limit value type (country of origin) : TGG 15 min / STEL ( NL )

Limit value : 100 ppm / 442 mg/m<sup>3</sup>

Remark : H

Version :

Limit value type (country of origin) : TGG 8 uur / TWA ( NL )

Limit value : 47,5 ppm / 210 mg/m<sup>3</sup>

Remark : H

Version :

Limit value type (country of origin) : TWA ( NZ )

Limit value : 50 ppm / 217 mg/m<sup>3</sup>

Remark : oto; bio

Version :

Limit value type (country of origin) : NDSCH ( PL )

Limit value : 200 mg/m<sup>3</sup>

Remark : skóra

Version :

Limit value type (country of origin) : NDS ( PL )

Limit value : 100 mg/m<sup>3</sup>

Remark : skóra

Version :

Limit value type (country of origin) : STEL ( ROK )

Limit value : 150 ppm

Version :

Limit value type (country of origin) : TWA ( ROK )

Limit value : 100 ppm

Version :

Limit value type (country of origin) : ACGIH TLV ( USA )

Limit value : 20 ppm

Remark : A4, OTO

Version :

Limit value type (country of origin) : OSHA PEL TWA ( USA )

Limit value : 100 ppm / 435 mg/m<sup>3</sup>

Remark : Appendix G (STEL 150 ppm, 655 mg/m<sup>3</sup>)

Version :

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : KZW ( A )

Limit value : 200 ppm / 880 mg/m<sup>3</sup>

Peak limitation : 5Mow, 8x

Remark : H

Version :

Limit value type (country of origin) : TMW / TWA ( A )

Limit value : 100 ppm / 440 mg/m<sup>3</sup>

Remark : H

Version :



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

---

Limit value type (country of origin) : TWA ( AUS )  
Limit value : 20 ppm / 87 mg/m<sup>3</sup>  
Remark : OTO  
Version :

Limit value type (country of origin) : STEL ( B )  
Limit value : 125 ppm / 551 mg/m<sup>3</sup>  
Remark : D  
Version :

Limit value type (country of origin) : TWA ( B )  
Limit value : 20 ppm / 87 mg/m<sup>3</sup>  
Remark : D  
Version :

Limit value type (country of origin) : BAT ( CH )  
Parameter : Urine (U) / End of exposure or end of shift  
Limit value : 600 mg/g Creatinine  
Version :

Limit value type (country of origin) : KZG / STEL ( CH )  
Limit value : 50 ppm / 220 mg/m<sup>3</sup>  
Remark : H, OL, B  
Version :

Limit value type (country of origin) : MAK ( CH )  
Limit value : 50 ppm / 220 mg/m<sup>3</sup>  
Remark : H, OL, B  
Version :

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H, Y  
Version : 17.06.2024

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift  
Limit value : 250 mg/g Creatinine  
Version : 10.10.2024

Limit value type (country of origin) : TWA ( DK )  
Limit value : 50 ppm / 217 mg/m<sup>3</sup>  
Remark : EHK  
Version :

Limit value type (country of origin) : VLA-EC / STEL ( E )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : via dérmica, VLB, VLI  
Version :

Limit value type (country of origin) : VLA-ED / TWA ( E )  
Limit value : 100 ppm / 441 mg/m<sup>3</sup>  
Remark : via dérmica, VLB, VLI  
Version :

Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : Skin  
Version : 09.03.2022

Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Skin  
Version : 09.03.2022

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

---

Limit value type (country of origin) : VLEP 8h / TWA ( F )  
Limit value : 20 ppm / 88,4 mg/m<sup>3</sup>  
Version :

Limit value type (country of origin) : VLEP CT / STEL ( F )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Version :

Limit value type (country of origin) : STEL ( GB )  
Limit value : 125 ppm / 552 mg/m<sup>3</sup>  
Remark : Sk  
Version :

Limit value type (country of origin) : TWA ( GB )  
Limit value : 100 ppm / 441 mg/m<sup>3</sup>  
Remark : Sk  
Version :

Limit value type (country of origin) : ÁK ( H )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : b, i, BEM  
Version :

Limit value type (country of origin) : CK-érték / STEL ( H )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : b, i, BEM  
Version :

Limit value type (country of origin) : STEL ( I )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : Cute  
Version :

Limit value type (country of origin) : TWA ( I )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Cute  
Version :

Limit value type (country of origin) : OELV 15 min / STEL ( IRL )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : Sk, IOELV  
Version :

Limit value type (country of origin) : OELV 8h / TWA ( IRL )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Sk IOELV  
Version :

Limit value type (country of origin) : TWA ( N )  
Limit value : 5 ppm / 20 mg/m<sup>3</sup>  
Remark : HKE  
Version :

Limit value type (country of origin) : TGG 15 min / STEL ( NL )  
Limit value : 97,3 ppm / 430 mg/m<sup>3</sup>  
Remark : H  
Version :

Limit value type (country of origin) : TGG 8 uur / TWA ( NL )  
Limit value : 48,6 ppm / 215 mg/m<sup>3</sup>  
Remark : H  
Version :

Limit value type (country of origin) : STEL ( NZ )  
Limit value : 40 ppm / 176 mg/m<sup>3</sup>  
Remark : skin; oto

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Flagstone-Sealant

Revision date : 04.06.2025

Version (Revision) :

6.0.0 (5.2.2)

Print date : 11.07.2025

Version :

Limit value type (country of origin) : TWA ( NZ )

Limit value : 20 ppm / 88 mg/m<sup>3</sup>

Remark : skin; oto

Version :

Limit value type (country of origin) : NDSCH ( PL )

Limit value : 400 mg/m<sup>3</sup>

Remark : skóra

Version :

Limit value type (country of origin) : NDS ( PL )

Limit value : 200 mg/m<sup>3</sup>

Remark : skóra

Version :

Limit value type (country of origin) : STEL ( ROK )

Limit value : 125 ppm

Remark : 발암성 2

Version :

Limit value type (country of origin) : TWA ( ROK )

Limit value : 100 ppm

Remark : 발암성 2

Version :

Limit value type (country of origin) : ACGIH TLV ( USA )

Limit value : 20 ppm

Remark : A3, OTO

Version :

Limit value type (country of origin) : NIOSH REL STEL ( USA )

Limit value : 125 ppm / 545 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : NIOSH REL TWA ( USA )

Limit value : 100 ppm / 435 mg/m<sup>3</sup>

Version :

Limit value type (country of origin) : OSHA PEL TWA ( USA )

Limit value : 100 ppm / 435 mg/m<sup>3</sup>

Remark : see Appendix G (STEL 125 ppm)

Version :

### DNEL-/PNEC-values

#### DNEL/DMEL

Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6)

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 11 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 11 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 32 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

---

|                      |                        |
|----------------------|------------------------|
| Limit value :        | 25 mg/kg               |
| Limit value type :   | DNEL worker (systemic) |
| Exposure route :     | Inhalation             |
| Exposure frequency : | Long-term              |
| Limit value :        | 150 mg/m <sup>3</sup>  |

XYLENE ; CAS No. : 1330-20-7

|                      |                       |
|----------------------|-----------------------|
| Limit value type :   | DNEL Consumer (local) |
| Exposure route :     | Inhalation            |
| Exposure frequency : | Short-term            |
| Limit value :        | 260 mg/m <sup>3</sup> |

|                      |                        |
|----------------------|------------------------|
| Limit value type :   | DNEL Consumer (local)  |
| Exposure route :     | Inhalation             |
| Exposure frequency : | Long-term              |
| Limit value :        | 65,3 mg/m <sup>3</sup> |

|                      |                          |
|----------------------|--------------------------|
| Limit value type :   | DNEL Consumer (systemic) |
| Exposure route :     | Oral                     |
| Exposure frequency : | Long-term                |
| Limit value :        | 5 mg/kg bw/day           |

|                      |                          |
|----------------------|--------------------------|
| Limit value type :   | DNEL Consumer (systemic) |
| Exposure route :     | Dermal                   |
| Exposure frequency : | Long-term                |
| Limit value :        | 125 mg/kg bw/day         |

|                      |                          |
|----------------------|--------------------------|
| Limit value type :   | DNEL Consumer (systemic) |
| Exposure route :     | Inhalation               |
| Exposure frequency : | Short-term               |
| Limit value :        | 260 mg/m <sup>3</sup>    |

|                      |                          |
|----------------------|--------------------------|
| Limit value type :   | DNEL Consumer (systemic) |
| Exposure route :     | Inhalation               |
| Exposure frequency : | Long-term                |
| Limit value :        | 65,3 mg/m <sup>3</sup>   |

|                      |                       |
|----------------------|-----------------------|
| Limit value type :   | DNEL worker (local)   |
| Exposure route :     | Inhalation            |
| Exposure frequency : | Short-term            |
| Limit value :        | 442 mg/m <sup>3</sup> |

|                      |                       |
|----------------------|-----------------------|
| Limit value type :   | DNEL worker (local)   |
| Exposure route :     | Inhalation            |
| Exposure frequency : | Long-term             |
| Limit value :        | 221 mg/m <sup>3</sup> |

|                      |                        |
|----------------------|------------------------|
| Limit value type :   | DNEL worker (systemic) |
| Exposure route :     | Dermal                 |
| Exposure frequency : | Long-term              |
| Limit value :        | 212 mg/kg bw/day       |

|                      |                        |
|----------------------|------------------------|
| Limit value type :   | DNEL worker (systemic) |
| Exposure route :     | Inhalation             |
| Exposure frequency : | Short-term             |
| Limit value :        | 442 mg/m <sup>3</sup>  |

|                      |                        |
|----------------------|------------------------|
| Limit value type :   | DNEL worker (systemic) |
| Exposure route :     | Inhalation             |
| Exposure frequency : | Long-term              |
| Limit value :        | 221 mg/m <sup>3</sup>  |

ETHYLBENZENE ; CAS No. : 100-41-4

|                      |                          |
|----------------------|--------------------------|
| Limit value type :   | DNEL Consumer (systemic) |
| Exposure route :     | Oral                     |
| Exposure frequency : | Long-term                |
| Limit value :        | 1,6 mg/kg bw/day         |

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 15 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 293 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 180 mg/kg bw/day

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 77 mg/m<sup>3</sup>

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ;  
CAS No. : 1065336-91-5

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 0,18 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 0,9 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 0,31 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 1,8 mg/kg bw/day

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 1,27 mg/m<sup>3</sup>

A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL- HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXPHENYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPPPLY(OXYETHYLENE)

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral

Exposure frequency : Long-term

Limit value : 0,025 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 0,25 mg/kg bw/day

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 0,085 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025  
**Print date :** 11.07.2025

**Version (Revision) :** 6.0.0 (5.2.2)

Exposure frequency : Long-term  
Limit value : 0,5 mg/kg bw/day  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 0,35 mg/m<sup>3</sup>

**PNEC**

XYLENE ; CAS No. : 1330-20-7

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,044 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 0,01 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,004 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 2,52 mg/kg dw  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 2,52 mg/kg dw  
Limit value type : PNEC (Soil)  
Limit value : 0,852 mg/kg dw  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 1,6 mg/l

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,1 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,01 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 13,7 mg/kg dw  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 1,37 mg/kg dw  
Limit value type : PNEC (Soil)  
Limit value : 2,68 mg/kg dw  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 9,6 mg/l

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ;  
CAS No. : 1065336-91-5

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,002 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 0,009 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,0002 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 1,05 mg/kg dw  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 0,11 mg/kg dw  
Limit value type : PNEC (Soil)  
Limit value : 0,21 mg/kg dw  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 1 mg/l

A MIXTURE OF: ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL- HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXYPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPPPLY(OXYETHYLENE)

Limit value type : PNEC (Aquatic, freshwater)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Flagstone-Sealant

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

|                    |                                      |
|--------------------|--------------------------------------|
| Limit value :      | 0,002 mg/l                           |
| Limit value type : | PNEC (Aquatic, intermittent release) |
| Limit value :      | 0,028 mg/l                           |
| Limit value type : | PNEC (Aquatic, marine water)         |
| Limit value :      | 0,0002 mg/l                          |
| Limit value type : | PNEC (Sediment, freshwater)          |
| Limit value :      | 3,37 mg/kg dw                        |
| Limit value type : | PNEC (Sediment, marine water)        |
| Limit value :      | 0,337 mg/kg dw                       |
| Limit value type : | PNEC (Soil)                          |
| Limit value :      | 2 mg/kg dw                           |
| Limit value type : | PNEC (Sewage treatment plant)        |
| Limit value :      | 10 mg/l                              |

## 8.2 Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

### Personal protection equipment

#### Eye/face protection

##### Suitable eye protection

Eye glasses with side protection goggles

##### Required properties

EN 166

#### Skin protection

##### Hand protection

**Suitable gloves type :** Gloves with long cuffs

**Suitable material :** Data apply to the main component. FKM (fluoro rubber), 0,7mm, >8h;

**Required properties :** EN ISO 374

**Recommended glove articles :** Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

**Additional hand protection measures :** Check leak tightness/impermeability prior to use.

**Remark :** Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

##### Body protection

Protective clothing.

**Suitable protective clothing :** Chemical protection clothing Chemical resistant safety shoes

**Required properties :** antistatic.

Protective clothing. : EN 13034 EN 14605

Chemical resistant safety shoes : EN ISO 20345

**Remark :** Barrier creams are not substitutes for body protection.

#### Respiratory protection

Usually no personal respiratory protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

##### Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (EN 136/140) Combination filtering device ABEK-P1

##### Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

### General information

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Flagstone-Sealant

Revision date : 04.06.2025

Version (Revision) :

6.0.0 (5.2.2)

Print date : 11.07.2025

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

**Appearance :** viscous

**Colour :** colourless

**Odour :** solvent

#### Safety characteristics

**Melting point/freezing point :** ( 1013 hPa ) < -13 °C

**Initial boiling point and boiling range :** ( 1013 hPa ) approx. 145 °C

**Decomposition temperature :** ( 1013 hPa ) not determined

**Flash point :** approx. 37 °C closed cup (EN ISO 3679)

**Auto-ignition temperature :** not determined

**Sustaining combustion** Yes UN Test L2:Sustained combustibility test

**Lower explosion limit :** not determined

**Upper explosion limit :** not determined

**Vapour pressure :** ( 50 °C ) < 3000 hPa

**Density :** ( 20 °C ) 0,9 g/cm<sup>3</sup> Pyknometer (DIN EN ISO 2811-1)

**Relative density :** ( 20 °C ) not determined

**Solvent separation test :** ( 20 °C ) < 3 % Test L1: Solvent separation test (UN)

**Water solubility** ( 20 °C ) immiscible

**Fat solubility :** ( 20 °C ) Not determined.

**pH :** not applicable DIN 19268

**log P O/W :** not determined (Mixture) ISO cup 4 mm (DIN EN ISO 2431)

**Flow time :** ( 23 °C ) approx. 32 s

**Odour threshold :** not determined

**Vapourisation rate :** not determined

**VOC content-EC** 81 Weight-% \*

**VOC content-EC** 730 g/l \*

**VOC-France** A+ Décret no 2011-321 du 23 mars 2011

**Flammable solids :** Not determined.

(\* VOC-EC = „Volatile organic compound (VOC)“ means any organic compound having an initial boiling point less than or equal to 250°C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

#### 9.2 Other information

Data apply to the main component:

Hydrocarbons, C9, aromatics (CAS: 64742-95-6)

Lower explosion limit (Vol-%): 0,6

Upper explosion limit (Vol-%): 7,0

log P O/W: 3,7 - 4,5

### SECTION 10: Stability and reactivity



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Flagstone-Sealant

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

## 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

## 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

## 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

## 10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

## 10.5 Incompatible materials

No data available

## 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

##### Acute oral toxicity

|                  |                                                                                                                                                                                                                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Parameter :      | LD50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )                                                                                                                                                                                                                                      |
| Exposure route : | Oral                                                                                                                                                                                                                                                                                               |
| Species :        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose : | > 2000 - 5000 mg/kg                                                                                                                                                                                                                                                                                |
| Parameter :      | LD50 ( XYLENE ; CAS No. : 1330-20-7 )                                                                                                                                                                                                                                                              |
| Exposure route : | Oral                                                                                                                                                                                                                                                                                               |
| Species :        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose : | 3523 mg/kg                                                                                                                                                                                                                                                                                         |
| Parameter :      | LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )                                                                                                                                                                                                                                                         |
| Exposure route : | Oral                                                                                                                                                                                                                                                                                               |
| Species :        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose : | 3500 mg/kg                                                                                                                                                                                                                                                                                         |
| Parameter :      | LD50 ( Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; CAS No. : 1065336-91-5 )                                                                                                                                           |
| Exposure route : | Oral                                                                                                                                                                                                                                                                                               |
| Species :        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose : | 3230 mg/kg                                                                                                                                                                                                                                                                                         |
| Method :         | OECD 423                                                                                                                                                                                                                                                                                           |
| Parameter :      | LD50 ( A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXYPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE) ) |
| Exposure route : | Oral                                                                                                                                                                                                                                                                                               |
| Species :        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose : | > 5000 mg/kg                                                                                                                                                                                                                                                                                       |
| Method :         | OECD 401                                                                                                                                                                                                                                                                                           |

##### Acute dermal toxicity

|                  |                                                               |
|------------------|---------------------------------------------------------------|
| Parameter :      | LD50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) ) |
| Exposure route : | Dermal                                                        |
| Species :        | Rabbit                                                        |
| Effective dose : | > 2000 mg/kg                                                  |
| Method :         | OECD 402                                                      |
| Parameter :      | LD50 ( XYLENE ; CAS No. : 1330-20-7 )                         |

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

## Trade name : Lithofin MN Flagstone-Sealant

Revision date : 04.06.2025

Version (Revision) :

6.0.0 (5.2.2)

Print date : 11.07.2025

|                                  |                                                                                                                                                                                                                                                                                                    |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Exposure route :                 | Dermal                                                                                                                                                                                                                                                                                             |
| Species :                        | Rabbit                                                                                                                                                                                                                                                                                             |
| Effective dose :                 | 12126 mg/kg                                                                                                                                                                                                                                                                                        |
| Parameter :                      | LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )                                                                                                                                                                                                                                                         |
| Exposure route :                 | Dermal                                                                                                                                                                                                                                                                                             |
| Species :                        | Rabbit                                                                                                                                                                                                                                                                                             |
| Effective dose :                 | 15400 mg/kg                                                                                                                                                                                                                                                                                        |
| Parameter :                      | LD50 ( Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; CAS No. : 1065336-91-5 )                                                                                                                                           |
| Exposure route :                 | Dermal                                                                                                                                                                                                                                                                                             |
| Species :                        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose :                 | > 3000 mg/kg                                                                                                                                                                                                                                                                                       |
| Method :                         | OECD 402                                                                                                                                                                                                                                                                                           |
| Parameter :                      | LD50 ( A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXPHE- NYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPLY(OXYETHYLENE) ) |
| Exposure route :                 | Dermal                                                                                                                                                                                                                                                                                             |
| Species :                        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose :                 | > 2000 mg/kg                                                                                                                                                                                                                                                                                       |
| Method :                         | OECD 402                                                                                                                                                                                                                                                                                           |
| <b>Acute inhalation toxicity</b> |                                                                                                                                                                                                                                                                                                    |
| Parameter :                      | LC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )                                                                                                                                                                                                                                      |
| Exposure route :                 | Inhalation                                                                                                                                                                                                                                                                                         |
| Species :                        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose :                 | > 2 - 10 mg/l                                                                                                                                                                                                                                                                                      |
| Exposure time :                  | 4 h                                                                                                                                                                                                                                                                                                |
| Method :                         | OECD 403                                                                                                                                                                                                                                                                                           |
| Parameter :                      | LC50 ( XYLENE ; CAS No. : 1330-20-7 )                                                                                                                                                                                                                                                              |
| Exposure route :                 | Inhalation                                                                                                                                                                                                                                                                                         |
| Species :                        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose :                 | 27124 mg/m <sup>3</sup>                                                                                                                                                                                                                                                                            |
| Exposure time :                  | 4 h                                                                                                                                                                                                                                                                                                |
| Parameter :                      | LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )                                                                                                                                                                                                                                                         |
| Exposure route :                 | Inhalation                                                                                                                                                                                                                                                                                         |
| Species :                        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose :                 | 17629 mg/m <sup>3</sup>                                                                                                                                                                                                                                                                            |
| Exposure time :                  | 4 h                                                                                                                                                                                                                                                                                                |
| Parameter :                      | LC50 ( A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXPHE- NYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPLY(OXYETHYLENE) ) |
| Exposure route :                 | Inhalation                                                                                                                                                                                                                                                                                         |
| Species :                        | Rat                                                                                                                                                                                                                                                                                                |
| Effective dose :                 | > 5,8 mg/l                                                                                                                                                                                                                                                                                         |
| Exposure time :                  | 4 h                                                                                                                                                                                                                                                                                                |
| Method :                         | OECD 403                                                                                                                                                                                                                                                                                           |

### Specific effects (Longterm animal experiment)

There are no data available on the preparation/mixture itself.

### Corrosion

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

**Trade name : Lithofin MN Flagstone-Sealant**

Revision date : 04.06.2025  
Print date : 11.07.2025

Version (Revision) : 6.0.0 (5.2.2)

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**Repeated dose toxicity (subacute, subchronic, chronic)**

There are no data available on the preparation/mixture itself.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

No information available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity**

Toxic to aquatic life with long lasting effects.

**Acute (short-term) fish toxicity**

Parameter : LC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 9,2 mg/l

Exposure time : 96 hour(s)

Method : OECD 203

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 2,6 mg/l

Exposure time : 96 hour(s)

Parameter : LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 4,2 mg/l

Exposure time : 96 hour(s)

Parameter : LC50 ( Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; CAS No. : 1065336-91-5 )

Species : Fish

Evaluation parameter : Acute (short-term) fish toxicity

Effective dose : 0,97 mg/l

Exposure time : 96 hour(s)

Method : OECD 203

Parameter : LC50 ( A MIXTURE OF: ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXYPOLY(OXYETHYLENE), ALPHA-3-(3-

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHE- NYL)PROPIONYL-  
OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-  
HYDROXYPHENYL)PROPIONYLOXYPPPLY(OXYETHYLENE) )

Species : Fish  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 2,8 mg/l  
Exposure time : 96 hour(s)  
Method : DIN 38412 / part 15

**Chronic (long-term) fish toxicity**

Parameter : NOEC ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Species : Fish  
Evaluation parameter : Chronic (long-term) fish toxicity  
Effective dose : 1,23 mg/l  
Exposure time : 28 day(s)  
Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Fish  
Evaluation parameter : Chronic (long-term) fish toxicity  
Effective dose : 0,714 mg/l

**Acute (short-term) toxicity to aquatic invertebrates**

Parameter : EC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Species : Daphnia  
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates  
Effective dose : 3,2 mg/l  
Exposure time : 48 hour(s)  
Method : OECD 202

Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia  
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates  
Effective dose : 1 mg/l  
Exposure time : 48 hour(s)

Parameter : EC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Species : Daphnia  
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates  
Effective dose : 1,8 mg/l  
Exposure time : 48 hour(s)

Parameter : EC50 ( A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-  
HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXYPOLY(OXYETHYLENE), ALPHA-3-(3-  
(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHE- NYL)PROPIONYL-  
OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-  
HYDROXYPHENYL)PROPIONYLOXYPPPLY(OXYETHYLENE) )

Species : Daphnia  
Evaluation parameter : Acute (short-term) toxicity to aquatic invertebrates  
Effective dose : 4 mg/l  
Exposure time : 48 hour(s)

**Chronic (long-term) toxicity to aquatic invertebrate**

Parameter : NOEC ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )  
Species : Daphnia  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 2,14 mg/l  
Exposure time : 21 day(s)

Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia  
Evaluation parameter : Chronic (long-term) toxicity to aquatic invertebrate  
Effective dose : 0,96 mg/l  
Parameter : NOEC ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Species : Daphnia

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

|                        |                                                                                                                                                                                                                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation parameter : | Chronic (long-term) toxicity to aquatic invertebrate                                                                                                                                                                                                                                                 |
| Effective dose :       | 1 mg/l                                                                                                                                                                                                                                                                                               |
| Parameter :            | NOEC ( Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; CAS No. : 1065336-91-5 )                                                                                                                                             |
| Species :              | Daphnia                                                                                                                                                                                                                                                                                              |
| Evaluation parameter : | Chronic (long-term) toxicity to aquatic invertebrate                                                                                                                                                                                                                                                 |
| Effective dose :       | > 1 mg/l                                                                                                                                                                                                                                                                                             |
| Exposure time :        | 21 day(s)                                                                                                                                                                                                                                                                                            |
| Method :               | OECD 211                                                                                                                                                                                                                                                                                             |
| Parameter :            | NOEC ( A MIXTURE OF:ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-HYDROXYPHENYL)PROPIONYL-OMEGA-HYDROXYPOLY(OXYETHYLENE), ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHE- NYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT- BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPLY(OXYETHYLENE) ) |
| Species :              | Daphnia                                                                                                                                                                                                                                                                                              |
| Evaluation parameter : | Chronic (long-term) toxicity to aquatic invertebrate                                                                                                                                                                                                                                                 |
| Effective dose :       | 0,78 mg/l                                                                                                                                                                                                                                                                                            |
| Exposure time :        | 21 day(s)                                                                                                                                                                                                                                                                                            |
| Method :               | OECD 202                                                                                                                                                                                                                                                                                             |

**Acute (short-term) toxicity to algae and cyanobacteria**

|                        |                                                                                                                                                          |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Parameter :            | EC50 ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )                                                                                            |
| Species :              | Algae                                                                                                                                                    |
| Evaluation parameter : | Acute (short-term) toxicity to algae and cyanobacteria                                                                                                   |
| Effective dose :       | 3,8 mg/l                                                                                                                                                 |
| Exposure time :        | 72 hour(s)                                                                                                                                               |
| Method :               | OECD 201                                                                                                                                                 |
| Parameter :            | EC50 ( XYLENE ; CAS No. : 1330-20-7 )                                                                                                                    |
| Species :              | Algae                                                                                                                                                    |
| Evaluation parameter : | Acute (short-term) toxicity to algae and cyanobacteria                                                                                                   |
| Effective dose :       | 4,36 mg/l                                                                                                                                                |
| Exposure time :        | 72 hour(s)                                                                                                                                               |
| Parameter :            | EC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )                                                                                                               |
| Species :              | Algae                                                                                                                                                    |
| Evaluation parameter : | Acute (short-term) toxicity to algae and cyanobacteria                                                                                                   |
| Effective dose :       | 3,6 mg/l                                                                                                                                                 |
| Exposure time :        | 72 hour(s)                                                                                                                                               |
| Parameter :            | EC50 ( Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; CAS No. : 1065336-91-5 ) |
| Species :              | Algae                                                                                                                                                    |
| Evaluation parameter : | Acute (short-term) toxicity to algae and cyanobacteria                                                                                                   |
| Effective dose :       | 1,68 mg/l                                                                                                                                                |
| Exposure time :        | 72 hour(s)                                                                                                                                               |
| Method :               | OECD 201                                                                                                                                                 |

**Chronic (long-term) toxicity to aquatic algae and cyanobacteria**

|                        |                                                                 |
|------------------------|-----------------------------------------------------------------|
| Parameter :            | NOEC ( Hydrocarbons, C9, aromatics ; CAS No. : (64742-95-6) )   |
| Species :              | Algae                                                           |
| Evaluation parameter : | Chronic (long-term) toxicity to aquatic algae and cyanobacteria |
| Effective dose :       | 0,07 mg/l                                                       |
| Exposure time :        | 72 hour(s)                                                      |
| Parameter :            | NOEC ( XYLENE ; CAS No. : 1330-20-7 )                           |
| Species :              | Algae                                                           |
| Evaluation parameter : | Chronic (long-term) toxicity to aquatic algae and cyanobacteria |
| Effective dose :       | 0,44 mg/l                                                       |
| Parameter :            | NOEC ( ETHYLBENZENE ; CAS No. : 100-41-4 )                      |
| Species :              | Algae                                                           |
| Evaluation parameter : | Chronic (long-term) toxicity to aquatic algae and cyanobacteria |

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

Effective dose : 3,4 mg/l  
Parameter : NOEC ( Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; CAS No. : 1065336-91-5 )  
Species : Algae  
Evaluation parameter : Chronic (long-term) toxicity to aquatic algae and cyanobacteria  
Effective dose : 0,22 mg/l  
Exposure time : 72 hour(s)

**Sewage treatment plant**

Observe local regulations concerning effluent treatment.

**12.2 Persistence and degradability**

There are no data available on the preparation/mixture itself.

**Biodegradation**

There are no data available on the preparation/mixture itself.

**12.3 Bioaccumulative potential**

There are no data available on the preparation/mixture itself.

**12.4 Mobility in soil**

There are no data available on the preparation/mixture itself.

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6 Endocrine disrupting properties**

No information available.

**12.7 Other adverse effects**

There are no data available on the preparation/mixture itself.

**12.8 Additional ecotoxicological information**

**Additional information**

The product has not been tested.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

Dispose of waste according to applicable legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Directive 2008/98/EC (Waste Framework Directive)**

**Before intended use**

**Waste codes/waste designations according to EWC/AVV**

Waste code (EWC/AVV) : 07 01 04\* (other organic solvents, washing liquids and mother liquors)

**After intended use**

Do not allow to enter into surface water or drains. Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Delivery to an approved waste disposal company.

**Disposal operations**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

**Waste codes/waste designations according to EWC/AVV**

Waste code packaging: 15 01 10\*

**13.2 Additional information**

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

**SECTION 14: Transport information**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**

( EN / D )

**Trade name : Lithofin MN Flagstone-Sealant**

Revision date : 04.06.2025  
Print date : 11.07.2025

Version (Revision) : 6.0.0 (5.2.2)

**14.1 UN number or ID number**

UN 1993

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**

FLAMMABLE LIQUID, N.O.S. ( TURPENTINE SUBSTITUTE · XYLENE )

**Sea transport (IMDG)**

FLAMMABLE LIQUID, N.O.S. ( TURPENTINE SUBSTITUTE · XYLENE )

**Air transport (ICAO-TI / IATA-DGR)**

FLAMMABLE LIQUID, N.O.S. ( TURPENTINE SUBSTITUTE · XYLENE )

**14.3 Transport hazard class(es)**

**Land transport (ADR/RID)**

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler No.) :** 30  
**Tunnel restriction code :** D/E  
**Special Provisions :** 640E · LQ 5 I · E 1  
**Hazard label(s) :** 3 / N

**Sea transport (IMDG)**

**Class(es) :** 3  
**EmS-No. :** F-E / S-E  
**Special Provisions :** LQ 5 I · E 1  
**Hazard label(s) :** 3 / N

**Air transport (ICAO-TI / IATA-DGR)**

**Class(es) :** 3  
**Special Provisions :** E 1  
**Hazard label(s) :** 3

**14.4 Packing group**

III

**14.5 Environmental hazards**

**Land transport (ADR/RID) :** Yes  
**Sea transport (IMDG) :** Yes (P)  
**Air transport (ICAO-TI / IATA-DGR) :** Yes

**14.6 Special precautions for user**

None

**14.7 Maritime transport in bulk according to IMO instruments**

Not required.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)  
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures (clp)  
DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste (2000/532/EC)  
EN 2:1992 (DIN EN 2:2005-01)

**Authorisations and/or restrictions on use**

**Restrictions on use**

**Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)**

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Flagstone-Sealant

**Revision date :** 04.06.2025

**Version (Revision) :**

6.0.0 (5.2.2)

**Print date :** 11.07.2025

Use restriction according to REACH annex XVII, no. : 3, 40, 75

### Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).  
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### Other regulations (EU)

Regulation (EC) No. 648/2004 [Detergents regulation]

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC)

### Regulation (EU) 2024/590 on substances that deplete the ozone layer

Not listed/not relevant.

Contains the following substances that deplete the ozone layer: -

### Regulation (EC) 2019/1021 [POP Regulation]

Not listed/not relevant.

Name of the persistent organic pollutant (POP): -

### Regulation (EU) 2019/1148 (marketing and use of explosives precursors)

Not listed/not relevant.

### Regulation (EU) 649/2012 (PIC)

Not listed/not relevant.

Chemicals qualifying for PIC notification: -

### National regulations

Observe in addition any national regulations!

Germany:

TRGS 400 (Risk assessment for activities involving hazardous substances)

TRGS 500 (Protective measures)

TRGS 510 (Storage of hazardous substances in non-stationary containers)

TRGS 555 (Working instruction and information for workers)

### Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

### Other regulations, restrictions and prohibition regulations

#### Switzerland

#### VOCV-Regulation

Maximum VOC content (Switzerland) : 81 Weight-% according to VOCV

## 15.2 Chemical Safety Assessment

For this substance/mixture a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

02. Label elements · 03. Hazardous ingredients · 08. Occupational exposure limit values

### 16.2 Abbreviations and acronyms

|            |                                                                                     |
|------------|-------------------------------------------------------------------------------------|
| ABC-Pulver | Extinguishing powder for fire class A, B and C                                      |
| ABEK-P1    | combination filter                                                                  |
| ADR        | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| AVV        | Abfallverzeichnis-Verordnung (Waste Regulation)                                     |
| AWSV       | Ordinance on facilities for the handling of substances hazardous to water           |
| BGR        | BG rules and regulations                                                            |
| ca.        | circa                                                                               |
| CAS        | Chemical Abstracts Service                                                          |
| CLP        | classification, labelling and packaging                                             |
| CMR        | Carcinogen, mutagen or toxic for reproduction                                       |



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

### Trade name : Lithofin MN Flagstone-Sealant

Revision date : 04.06.2025

Version (Revision) :

6.0.0 (5.2.2)

Print date : 11.07.2025

|                     |                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------|
| DIN                 | German Institute for Standardization                                                                |
| DNEL                | Derived No-Effect Level                                                                             |
| EAK/EWC/EAC/CWR/CER | European Waste Catalogue                                                                            |
| EC50 / CE50         | Effective Concentration 50%                                                                         |
| EG / EC / CE        | European Community                                                                                  |
| EN                  | European Standard                                                                                   |
| EUH                 | supplemental hazard statement of the european union                                                 |
| GefStoffV           | Gefahrstoffverordnung (Hazardous Substances Ordinance)                                              |
| GHS / SGH           | Globally Harmonised System                                                                          |
| H-Sätze             | hazard statements                                                                                   |
| IATA-DGR            | International Air Transport Association-Dangerous Goods Regulations                                 |
| IBC-Code            | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |
| ICAO-TI             | International Civil Aviation Organization-Technical Instructions                                    |
| IMDG-Code           | International Maritime Dangerous Goods Code                                                         |
| ISO                 | International Organization for Standardization                                                      |
| LC50 / CL50         | Lethal Concentration 50%                                                                            |
| LD50 / DL50         | Lethal Dose 50%                                                                                     |
| log P O/W           | Partition coefficient n-octanol/water                                                               |
| MARPOL              | International Convention for the Prevention of Pollution from Ships (marine pollution)              |
| NOAEL (DSET)        | No observed adverse effect level                                                                    |
| NOEC (CSEO)         | No observed effect concentration                                                                    |
| Nr.                 | Number                                                                                              |
| OECD                | Organisation for Economic Co-operation and Development                                              |
| PBT                 | persistent, bioaccumulative and toxic                                                               |
| pH                  | Potentia hydrogenii                                                                                 |
| PIC                 | prior informed consent                                                                              |
| PNEC                | Predicted No-Effect Concentration                                                                   |
| POP                 | Persistent organic pollutants                                                                       |
| P-Sätze             | precautionary statements                                                                            |
| REACH               | Registration, Evaluation, Authorisation and Restriction of Chemicals                                |
| RID                 | International Carriage of Dangerous Goods by Rail                                                   |
| STEL / LECT         | short-term exposure limit                                                                           |
| TRGS                | Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)                       |
| TWA / MPT           | time-weighted average                                                                               |
| UN/ONU              | United Nations                                                                                      |
| VOC/COV/VOS/LZO     | Volatile Organic Compound                                                                           |
| VOCV                | Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)                           |
| vPvB                | very persistent and very bioaccumulative                                                            |
| WGK                 | Wassergefährdungsklasse (Water hazard class)                                                        |

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

### 16.3 Key literature references and sources for data

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

ECHA: Registered substances (<https://echa.europa.eu/information-on-chemicals/registered-substances>)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

( EN / D )

**Trade name :** Lithofin MN Flagstone-Sealant

**Revision date :** 04.06.2025

**Version (Revision) :** 6.0.0 (5.2.2)

**Print date :** 11.07.2025

REACH Article 59: Candidate List of substances of very high concern for Authorisation  
(<https://echa.europa.eu/candidate-list-table>)

### 16.4 **Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

Hazard statements for physical hazards : On basis of test data.

Hazard statements for health hazards : Calculation method.

Hazard statements for environmental hazards : Calculation method.

### 16.5 **Relevant H- and EUH-phrases (Number and full text)**

|        |                                                                    |
|--------|--------------------------------------------------------------------|
| H225   | Highly flammable liquid and vapour.                                |
| H226   | Flammable liquid and vapour.                                       |
| H304   | May be fatal if swallowed and enters airways.                      |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.                                            |
| H317   | May cause an allergic skin reaction.                               |
| H332   | Harmful if inhaled.                                                |
| H335   | May cause respiratory irritation.                                  |
| H336   | May cause drowsiness or dizziness.                                 |
| H361d  | Suspected of damaging the unborn child.                            |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H400   | Very toxic to aquatic life.                                        |
| H410   | Very toxic to aquatic life with long lasting effects.              |
| H411   | Toxic to aquatic life with long lasting effects.                   |
| H412   | Harmful to aquatic life with long lasting effects.                 |
| EUH066 | Repeated exposure may cause skin dryness or cracking.              |

### 16.6 **Training advice**

None

### 16.7 **Additional information**

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.